



GROUP NO.	PART NO.	PERFORMANCE LEVEL				WEIGHT (kgs)	MAXIMUM OVERALL DIMENSIONS					
		CCA	R.C.	REF. CA	20 HR CAP		LENGTH		WIDTH		HEIGHT	
							in	mm	in	mm	in	mm
<b>12-VOLT LAWN MOWER — GARDEN TRACTOR — SMALL ENGINE CALCIUM MAINTENANCE-FREE</b>												
U1	7U1L	195		240	26 (*)	6,81		197		130		184
U1R	7U1R	195		240	26 (*)	6,81		197		130		184
U1	10U1L	300		370	30 (*)	7,72		197		130		184
U1R	10U1R	300		370	30 (*)	7,72		197		130		184
U1	11U1L	350		400	32 (*)	8,62		197		130		184
U1R	11U1R	350		400	32 (*)	8,62		197		130		184
GROUP NO.	PART NO.	PERFORMANCE LEVEL				WEIGHT (kgs)	MAXIMUM OVERALL DIMENSIONS					
		CCA	R.C.	REF. CA	20 HR CAP		LENGTH		WIDTH		HEIGHT	
							in	mm	in	mm	in	mm
<b>12-VOLT — AGM VALVE REGULATED</b>												
34	9A34	775	120	890	55	19,30		273		175		203
34R	9A34R	775	120	955	55	19,30		273		175		203
34/78	9A78DT	775	120	955	55	19,52		273		175		203
L2	9AGM47	600	100	690	60	17,7		242		175		190
L3	9AGM48	760	120	875	70	20,7		278		175		190
L4	9AGM94R	800	140	920	80	23,6		315		175		190
L5	9AGM49	850	170	975	92	26,33		354		175		190
L6	9AGM95R	950	190	1050	105	29,28		394		175		190
31P	9A31P	925	190	1050	100	30,2		330		171		241
<b>12-VOLT — AGM VALVE REGULATED</b>												
MIATA	8AMU1R	320	45	400	—	10,9		197		130		184
PRIUS	9A51P	325	60	390	46	13,4		235		127		220
GROUP NO.	PART NO.	PERFORMANCE LEVEL				WEIGHT (kgs)	MAXIMUM OVERALL DIMENSIONS					
		CCA	R.C.	REF. CA	20 HR CAP		LENGTH		WIDTH		HEIGHT	
							in	mm	in	mm	in	mm
<b>12-VOLT ULTIMATE® ADVANCED GENERATION / A3™ TECHNOLOGY</b>												
75	775DT	690	95	850	60 (*)	16,57		248		178		206
75	775MF	690	95	850	60 (*)	16,34		248		178		184
78	778DT	800	115	985	75 (*)	19,07		273		175		203
78	778MF	800	115	985	75 (*)	18,61		273		175		184
34	734MF	800	115	985	75 (*)	18,61		273		175		203
34	734RMF	800	115	985	75 (*)	18,61		273		175		203
79	779MF	840	140	1035	100 (*)	19,52		307		179		188
27	727MF	840	140	1035	100 (*)	23,15		321		171		229
27F	727FMF	840	140	1035	100 (*)	23,15		321		171		229
<b>12-VOLT GOLD / A3™ TECHNOLOGY</b>												
96	696RMF							242		175		175
47 L2	647MF	600	95	740	60	16,8		242		175		190
48 L3	648MF	680	120	835	70	19,30		278		175		190
91 (T6)	691MF	700	100	860	50	17,5		278		175		175
94R L4	694RMF	765	135	940	80	21,56		315		175		190
49 L5	649MF	900	185	1105	100	23,83		354		175		190
92	692MF											
95R L6	695RMF	850	190	1045	110	27,92	15-1/2	394		175		190
<b>12-VOLT PREMIUM / A3™ TECHNOLOGY</b>												
51	551MF	450	70	550	55 (*)	12,94		238		127		222
51R	551RMF	450	70	550	55 (*)	12,94		238		127		222
26	526MF	540	80	665	55 (*)	14,07		222		171		203
26R	526RMF	540	80	665	55 (*)	14,07		222		171		203
GROUP NO.	PART NO.	PERFORMANCE LEVEL				WEIGHT (kgs)	MAXIMUM OVERALL DIMENSIONS					
		CCA	R.C.	REF. CA	20 HR CAP		LENGTH		WIDTH		HEIGHT	
							in	mm	in	mm	in	mm
<b>6-VOLT HEAVY-DUTY COMMERCIAL SERVICE</b>												
1	901MF	640	130	785	105 (*)	15	9	229	6-7/8	175	8-3/4	222
<b>12-VOLT HEAVY-DUTY COMMERCIAL SERVICE</b>												
31	1131PMF	950	175	1170	105 (*)	25,65		330		171		241
31	1231PMF	100	185	1230	115 (*)	27,24						
31	7T31P	730	190	900	115 (*)	28,2		330		171		241
4D	904D	1050	290	1290	180 (*)	44,03		527		216		258
8D	908DFT	1425	440	1755	240 (*)	57,66		527		279		254
GROUP NO.	PART NO.	PERFORMANCE LEVEL				WEIGHT (kgs)	MAXIMUM OVERALL DIMENSIONS					
		CCA	R.C.	REF. CA	20 HR CAP		LENGTH		WIDTH		HEIGHT	
							in	mm	in	mm	in	mm
<b>12-VOLT MARINE / RV STARTING CALCIUM MAINTENANCE-FREE</b>												
24	24M7	800	130	1000	80 (*)	20,43		273		171		238
27	27M6	840	182	1050	90 (*)	26,1		318		171		238
GROUP NO.	PART NO.	PERFORMANCE LEVEL				WEIGHT (kgs)	MAXIMUM OVERALL DIMENSIONS					
		CCA	R.C.	REF. CA	20 HR CAP		LENGTH		WIDTH		HEIGHT	
							in	mm	in	mm	in	mm

GROUP NO.	PART NO.	CCA	MIN @25A	REF. CA	20 HR CAP	WEIGHT (kgs)	LENGTH		WIDTH		HEIGHT	
							in	mm	in	mm	in	mm
<b>12-VOLT MARINE / RV DEEP CYCLE SERVICE</b>												
24	DC24	500	130	615	75	20,66		273		171		238
27	DC27	575	175	705	90	24,30		318		171		238
31	DC31DT	650	185	800	105	27,24		330		171		241
GROUP NO.	PART NO.	PERFORMANCE LEVEL				WEIGHT (kgs)	MAXIMUM OVERALL DIMENSIONS					
		CCA	MIN @75A	REF. CA	20 HR CAP		LENGTH		WIDTH		HEIGHT	
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	
<b>6-VOLT EV — MOTIVE POWER — DEEP CYCLE SERVICE</b>												
GC2	GC15		120		230	29,06		260		181		276
901	9C11		130		250	33,14						292
902	8C6V		170		330	44,26		298		178		365
903	8L16		190		370	50,40						419
<b>8-VOLT EV — MOTIVE POWER — DEEP CYCLE SERVICE</b>												
GC8	GC8V		85		165	30,87		260		181		283
<b>12-VOLT EV — MOTIVE POWER — DEEP CYCLE SERVICE</b>												
	GC12V		77		155	40,86		333		179		289
921	9C12		115		228	57,66		394		178		362
GROUP NO.	PART NO.	PERFORMANCE LEVEL				WEIGHT (kgs)	MAXIMUM OVERALL DIMENSIONS					
		CCA	R.C.	REF. CA	20 HR CAP		LENGTH		WIDTH		HEIGHT	
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	
<b>12V GEL VALVE REGULATED</b>												
U1	8GU1	200	44	290	31,6	10,44		197		130		184
	8G40C	225	59	325	40	14,53		197		168		175
22NF	8G22NF	210	77	300	51	16,8		238		140		238
34R	8G34R	300	90	420	60	17,7		259		168		178
24	8G24	335	132	470	73,6	23,6		276		171		251
24SS	8G24SS	335	132	470	73,6	23,6		260		171		210
27	8G27							326		171		236
31M	8G31DTM	550	780	180	97,6	31,78		329		171		238
5SHP	8G5SHP				115	38,59		345		171		290
4D	8G4D	970	375	1245	183	62,2		527		216		258
8D	8G8D	1150	475	1470	225	75,364		527		279		254
<b>6V GEL VALVE REGULATED</b>												
GC2	8GGC2	585	345	850	180	30,87		260		181		276
<b>8V GEL VALVE REGULATED</b>												
GC8	8G8VGC	400	250	575	250	31,78		260		181		276
<b>12V AGM VALVE REGULATED</b>												
U1	8AU1H	200	45	240	32	10,89		197		130		184
22NF	8A22NF	350	85	420	55	17,7		238		140		238
24	8A24	335	132	470	73,6	23,6		276		171		251
27	8A27							326		171		236
31M	8A31DTM	800	1000	200	105	31,32		329		171		238
4D	8A4D	1110	380	1420	198	59,47		527		216		258
8D	8A8D	1450	480	1800	245	73,1		527		279		254
GC2	8AGC2	680	380	900	190	31,78		260		181		276
GROUP NO.	PART NO.	PERFORMANCE LEVEL				WEIGHT (kgs)	MAXIMUM OVERALL DIMENSIONS					
		CCA	R.C.	REF. CA	10 HR CAP		LENGTH		WIDTH		HEIGHT	
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	
<b>POWER SPORTS AGM VALVE REGULATED</b>												
	ETX9	120			8	3,3		150		88		106
	ETX12	180			10	4,3		150		88		130
	ETX14	220			12	5,4		150		88		145
	ETX14L	220			12	5,4		150		88		145
	ETX15	220			14	5,1		134		90		166
	ETX15L	220			14	5,1		134		90		166
	ETX16	325			19	7,7		175		100		155
	ETX16L	325			19	7,7		175		100		155
	ETX18L	340			20	8,2		206		91		163
	ETX20L	310			17,5	7		175		88		155
	ETX30L	400			26	9,8		168		131		175